

CODA S5.5 specs

STEREO

Rated Power: 50 Watts Class A @ 8 Ohms

Frequency Response: -3dB @ DC to 100kHz

Distortion: < .04% from 10Hz to 20kHz @ 50W

Gain: 26dB

Maximum Current: 100 Amperes peak per channel

Noise: Less than 120dB referenced to rated output

Input Impedance: 50k Ohms unbalanced/10k Ohms balanced

Output Impedance: .04 Ohms from 20Hz to 20kHz

BRIDGED MONO

Rated Power: 200 Watts @ 8 Ohms

Frequency Response: -3dB @ DC to 100kHz

Distortion: < .04% from 10Hz to 20kHz @ 50W

Gain: 26dB

Maximum Current: 100 Amperes peak per channel

Noise: Less than 120dB referenced to rated output

Input Impedance: 50k Ohms unbalanced/10k Ohms balanced

Output Impedance: .04 Ohms from 20Hz to 20kHz

POWER SUPPLY

Transformer Type: Multi-tap, multi-winding toroidal

Transformer Rating: 1500 VA

Power Filtering: 80,000 microfarad

DIMENSIONS

Height: 5.75"

Width: 17.5"

Depth: 12.5"

Weight: 45 lbs

Power requirement: 450 Watts maximum at rated power